



### #GPC GROUND PEDESTAL CLAMP

A Signal Reference Grid may be economically fabricated from standard, bare round wire joined together via welding, brazing, compression or a suitable grounding clamp arrangement at each of the crossing points.\*

\*IEEE, Std. 1100-1999

#### DESCRIPTION

- Copper clamp fits both 1" round and square pedestal legs.
- Accepts #6 conductor, however, other sizes are available.
- Listed to UL 467 - Grounding and Bonding Equipment.
- Beware - some fastener manufacturers promote cheap wire hangers as signal reference grid wire clamps. These hangers are only designed (UL Listed) for wire positioning; they ARE NOT UL Listed for electrical grounding!

#### APPLICATIONS

- Used when fabricating signal reference grids under computer room floors.
- Bi-directional design reduces clamp requirements by 50%.

Catalog No.	U-Bolt Type	Pedestal Size	Conductor Size
GPC6SQ	Square	1"	#6 AWG
GPC6RD	Round	1"	#6 AWG
GPC4SQ	Square	1"	#4 AWG
GPC4RD	Round	1"	#4 AWG
GPC2SQ	Square	1"	#2 AWG
GPC2RD	Round	1"	#2 AWG

301 Ziegler Drive, Grayslake, IL 60030  
847-548-8700 • 800-842-7437 • Fax: 847-548-8755  
Web-site: [www.harger.com](http://www.harger.com) • E-mail: [hargersales@harger.com](mailto:hargersales@harger.com)